

## REMOTE DISCONNECT SYSTEMS FOR UTILITY METERS

**Related Applications:** This application is a continuation-in-part of serial number 09/672,162, filed on September 27, 2000.

**Field of the Invention:** This invention is in the field of disconnect systems for electrical power meters.

### Background of the Invention

Utility meters are widely used by utility companies to monitor the usage of electrical power into residences, offices, and any other sites using electrical power supplied by the utility companies. These meters are typically monitored by visual inspections and the customer billed according to their electrical usage. Often it becomes necessary for the power to be disconnected from the site being served. This may be due to an end of service situation, a chronic no-pay customer, seasonal use of the site being served, turn-over of a site or other situations. Presently, these situations require service personnel to visit the site and manually disconnect the power, such as removing the meter. An additional visit is required then to re-connect the power.

These visits are time-consuming and expensive for the utility companies. Further, the timing may not always be suitable for many situations, such as re-connecting power. An additional problem arises in situations where safety may be of concern.

A previous attempt to solve this problem is disclosed in U.S. Patent No. 5,668,538, issued to Warwick. This patent discloses a modular electricity meter having a remotely controllable switch. This meter uses a direct telephone connection or a radio signal to activate a solenoid switch. This system requires special installation and either the expense of a direct telephone line or special radio equipment to operate the device.

There presently is a need for a system that will provide remote disconnect/connect of a utility power supply in an inexpensive manner.

## Summary of the Invention

5

The present invention solves these problems and others by providing a system for remote disconnect/connection of electrical power into a building. The system, in a preferred embodiment, is a "plug and play" device that is already preprogrammed for operation. The system is integrally mounted within a utility power meter. The power meter is simply plugged into the meter housing and the control board is activated by any touch tone telephone or computer modem. Once the paging service has been activated, the system is ready for operation without the need of complicated installation or programming.

10

The user is then able to dial a pager number that is already pre-programmed. The paging service then transmits a signal to a radio frequency ("RF") receiver in the power supply module. The signal is then decoded and sent to a processor. The processor then causes a switching circuit to open or close in accordance with the decoded signal to disconnect or connect the electrical power entering the building. The exemplary embodiments are described using relay switches or other types of switching circuits.

15

20

These and other features will be evident from the ensuing description of preferred embodiments and from the drawings.

## Brief Description of the Drawings

Figure 1 illustrates a view of a preferred embodiment of the present invention.

5 Figure 2 shows a device utilizing the preferred embodiment of Figure 1.

Figure 3 illustrates a standard utility power meter set-up.

Figure 4 illustrates an operational diagram of a preferred embodiment of the present invention.

10 Figure 5 illustrates a schematic of the RF receiver, and filter of the preferred embodiment of Figure 1.

Figure 6 illustrates a schematic of the decoder circuit of the embodiment of Figure 1.

Figure 7 illustrates a command controller unit of the preferred embodiment of Figure 1.

15 Figure 8 illustrates a schematic of the switching circuit, input power supply unit and the output power supply unit of the preferred embodiment of Figure 1.

## Detailed Description of Preferred Embodiments

A preferred embodiment of the present invention is illustrated in Figures 1 – 8. It is to be expressly understood that the descriptive embodiments are provided herein for explanatory purposes only and is not meant to unduly limit the claimed inventions. The preferred embodiment of the present invention includes a wireless remote control system for disconnecting/connecting electrical power for houses, buildings and other environments using electrical meters. The preferred embodiment of the present invention has particular utility for seasonal use buildings, apartment complexes with high turn over rates, chronic no pays and for use in safety disconnect environments.

### General Overview

In a preferred embodiment, the present invention incorporates a wireless remote control system integrated within an electrical power meter, such as shown in Figure 1. The integrated utility meters 10, of the preferred embodiment of the present invention, are able to quickly replace existing standard utility meters. The utility meter 10, as shown in Figure 1 and Figure 2, meters the flow of electricity from a utility substation into a building, such as a house, office building, apartment complex, etc.

The utility meter 10 includes control board 20, as shown in Figure 3, integrated directly into the utility meter 10. The control board is shown in an operational diagram in Figure 4 and schematically in Figures 5 – 8. The control board 20 is connected between the power input loads 12, 14 and power output loads 16, 18.

The remote disconnection/connection system of a preferred embodiment includes an Electrical Input 30, Radio Frequency (“RF”) Receiver 40, Filter Circuit 50, Decoder Unit 60, Command Controller Unit 70, Switching Circuit 80 and Electrical Output 90. Each of these circuits will be discussed in greater detail below.

If the utility company decides to remotely power disconnect the electricity into the building, it only requires a simple telephone call. The user calls an assigned

telephone number to a paging service. The user may also use a mobile telephone, a personal computer, or even a personal digital assistant. The paging service then transmits an encrypted signal from a paging transmitter in accordance with standard paging technology. The signal can be transmitted from land or satellite based  
5 paging transmitters.

The paging signal is received at the control board 20 by RF receiver 40. The system may use an external antennae if necessary. The received paging signal is then filtered through filter circuit 50 and sent to decoding controller 60. The controller 60 then decodes the signal into a command stream. This command stream  
10 is sent to the Command Controller Unit 70.

The Command Controller Unit 70, in accordance with the command stream, then activates the Switching Circuit 80. Switching Circuit 80, in the preferred embodiment, is a relay switch. It is to be expressly understood that other types of circuits may be used as well to enable the switching operation. The Switching  
15 Circuit 80 is normally in the closed position so that the fail mode is powered on in the preferred embodiment. In this embodiment the Circuit 80 is in a closed position so the Electrical Output is hot. Thus, the Command Controller Unit 70, upon receiving the command signal processed from the signal sent by the paging transmitter based on the user's call, causes the Switching Circuit 80 to open. The  
20 current from the input power unit is interrupted and the Electrical Output 90 is no longer hot.

It is to be expressly understood that the reverse can also be accomplished under the present invention. The Switching Circuit 80 may be maintained normally in the open position so that power is not initially powered to the Electrical Output 90.  
25 The user can then power up any device connected to the Electrical Output 90 by simply paging the system, as discussed above. The Switching Circuit 80 is closed to allow current to flow to the main power output 90 to power up the device connect to it.

### **Specific Implementation of a Wireless Remote Control System**

A specific implementation of a wireless remote control activation system, as discussed above, is shown in Figures 5 - 8. It is to be expressly understood that this implementation is being described for explanatory purposes and is not meant to limit the claimed inventions.

RF Receiver 40 is schematically shown in Figure 5. The RF Receiver 40 is capable of receiving an RF signal from a paging transmitter (not shown). The paging transmitter can be land-based or satellite based. The RF Receiver 40 may be connected to an external antenna (not shown) if necessary. The paging transmitter transmits the RF signal based upon a user telephoning an assigned telephone number, or from a computer via a modem, personal digital assistant or other known devices for notifying the paging transmitter. The RF Receiver 40 receives the RF signal from the paging transmitter wherein it is sent through Filter 50 to initially process the signal. The filtered signal is then sent to Paging Decoder 60, shown in Figure 6, that decodes the RF signal from a typical paging protocol format. The transmitted signal is decoded into a digital bit stream and sent onward along buss 62 to the Command Controller 70, shown in Figure 7.

Command Controller 70 receives the digital bit stream and acts in accordance with the information contained in the stream. The Command Controller 70 includes an integrated processor circuit 72 to process the signal. Controller Unit 70 may also include an LED (Light Emitting Diode) 73 to display the status of the Unit. The serial interface 74 also allows the Command Controller Unit 70 be updated or reprogrammed. The Unit 70 also includes a buffer memory circuit 75 in the event that the Controller Unit memory bank is full.

Power Override Circuit 76 (in another preferred embodiment) is provided to allow the Command Controller Unit 70 to be overridden, such as to manually switch the power on or off to the Electrical Output 90. In normal use, the Command Controller Unit 70 transmits a command signal to the Switching Circuit 80, shown in Figure 8, in accordance with the paging transmitted signal. The Switching Circuit 80, normally held in the closed position would then be reset to the open position to prevent power from flowing to Electrical Output 90. Alternatively, if the failsafe

5

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---